



Repeats Not Shown to Scale.

Epic

Meets or exceeds all ACT® Standards

Made in the U.S.A
Crypton Seating Fabric
Bleach Cleanable
FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT® Registered Certification Marks



Fabric Specifications

Content	100% Polyester
Finish	Crypton®
Backing	Crypton®
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	14.7 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 160 per inch Picks: 36 per inch
Repeat	H - n/a V - 8.88"
Directional	Yes
Railroaded	Yes
Made in the USA	Yes

Additional Attributes

PFAS Free	Yes
-----------	-----

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	---

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

Performance Characteristics

Abrasion Resistance ASTM D4157	102,000 * double rubs
Brush Pill ASTM D3511	Class 4
Tensile Strength ASTM D5034	Warp: 87.0 lbs Fill: 91.0 lbs.
Tear Strength ASTM D2262	Warp: 32.0 lbs. Fill: 59.0 lbs.
Seam Slippage ASTM D4034	Warp: 35.0 lbs. Fill: 70.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	40 Hours Class 4

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.



Repeats Not Shown to Scale.

Folklore

Meets or exceeds all ACT® Standards

Made in the U.S.A
Crypton Seating Fabric
Bleach Cleanable
FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT® Registered Certification Marks



Fabric Specifications

Content	86% Post Consumer Recycled Polyester, 14% Polyester
Finish	Crypton® Green
Backing	Crypton® Green
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	25.0 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 160 per inch Picks: 54 per inch
Repeat	H - 14.4" V - 13.5"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Additional Attributes

PFAS Free	Yes
-----------	-----

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	--

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

Performance Characteristics

Abrasion Resistance ASTM D4157	105,000 * double rubs
Brush Pill ASTM D3511	Class 4
Tensile Strength ASTM D5034	Warp: 153.0 lbs Fill: 175.0 lbs.
Tear Strength ASTM D2262	Warp: 31.0 lbs. Fill: 37.0 lbs.
Seam Slippage ASTM D4034	Warp: 92.0 lbs. Fill: 94.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	40 Hours Class 4

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.



Repeats Not Shown to Scale.

Legend

Meets or exceeds all ACT® Standards

Made in the U.S.A
Crypton Seating Fabric
Bleach Cleanable
FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT® Registered Certification Marks



Fabric Specifications

Content	61% Post Consumer Recycled Polyester, 22% Polyester UV, 17% Polyester
Finish	Crypton® Green
Backing	Crypton® Green
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	20.0 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 80 per inch Picks: 30 per inch
Repeat	H - 2.50" V - 5.88"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Additional Attributes

PFAS Free	Yes
-----------	-----

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	---

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

Performance Characteristics

Abrasion Resistance ASTM D4157	105,000 * double rubs
Brush Pill ASTM D3511	Class 4
Tensile Strength ASTM D5034	Warp: 214.0 lbs Fill: 154.0 lbs.
Tear Strength ASTM D2262	Warp: 19.0 lbs. Fill: 16.0 lbs.
Seam Slippage ASTM D4034	Warp: 38.0 lbs. Fill: 43.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	40 Hours Class 4

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.