



Repeats Not Shown to Scale.

Canopy

Meets or exceeds all ACT® Standards

Crypton Green Seating Fabric
Bleach Cleanable
FR Free – Compliant with CAL AB 2998



*ACT® Registered Certification Marks



Fabric Specifications

Content	61% Post Consumer Recycled Polyester 39% Polyester
Finish	Crypton® Green
Backing	Crypton® Green
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	14.7
Width	54"
Roll Size	60 yards
Ends/Picks	160/84
Repeat	H 14.813" V 16.188"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Additional Attributes

FR Free	Yes
---------	-----

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	---

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

* Cleaning information is offered for general guidance and is not a guarantee. The use of certain cleaning agents can be harmful to the surface appearance and lifespan of a product. Burch Fabrics assumes no responsibility for damage to a product resulting from lack of cleaning, improper cleaning or the misuse of cleaning agents. Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to materials and cause permanent damage. Burch Fabrics cannot be held responsible for dye transfer caused by external contaminants.

Performance Characteristics

Abrasion Resistance ASTM D4157	63,000 * double rubs
Brush Pill ASTM D3511	Class 5
Tensile Strength ASTM D5034	Warp: 236.0 lbs Fill: 457.0 lbs.
Tear Strength ASTM D2261	Warp: 29.0 lbs. Fill: 55.0 lbs.
Seam Slippage ASTM D4034	Warp: 90.0 lbs. Fill: 115.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0
Colorfastness to Light AATCC 16	40 Hours Class 4

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.



Repeats Not Shown to Scale.

Rivulet

Meets or exceeds all ACT® Standards

Crypton Green Seating Fabric
Bleach Cleanable
FR Free – Compliant with CAL AB 2998



*ACT® Registered Certification Marks



Fabric Specifications

Content	82% Post Consumer Recycled Polyester 18% Nylon
Finish	Crypton® Green
Backing	Crypton® Green
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	15.3
Width	54"
Roll Size	60 yards
Ends/Picks	160/106
Repeat	H 30.188" V 28.63"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Additional Attributes

FR Free	Yes
---------	-----

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	---

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

* Cleaning information is offered for general guidance and is not a guarantee. The use of certain cleaning agents can be harmful to the surface appearance and lifespan of a product. Burch Fabrics assumes no responsibility for damage to a product resulting from lack of cleaning, improper cleaning or the misuse of cleaning agents. Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to materials and cause permanent damage. Burch Fabrics cannot be held responsible for dye transfer caused by external contaminants.

Performance Characteristics

Abrasion Resistance ASTM D4157	102,000 * double rubs
Brush Pill ASTM D3511	Class 5
Tensile Strength ASTM D5034	Warp: 202.0 lbs Fill: 452.0 lbs.
Tear Strength ASTM D2261	Warp: 32.0 lbs. Fill: 69.0 lbs.
Seam Slippage ASTM D4034	Warp: 93.0 lbs. Fill: 76.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	40 Hours Class 4

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.